

## 3.6 V Li-Ion

### IXO 3 Cordless Screwdriver (0 601 960 2L0)



Capacity	
Max. Screw Dia.	: 5 mm
Max. Torque	: 4 Nm
No-load Speed	: 0 - 180 rpm
Battery Voltage	: 3.6 V / 1.3 Ah
Charger	: AL 1115 CV
Charging Time	: about 5 hours
Weight	: 0.3 kg

### GSR 3,6 V-LI ProDrive Cordless Screwdriver (0 601 9A2 0L1)



Capacity	
Max. Screw Dia.	: 5 mm
Max. Torque	: 7 Nm
No-load Speed	: 0 - 250 rpm
Battery Voltage	: 3.6 V / 1.3 Ah
Charger	: AL 1115 CV
Charging Time	: 60 mins
Weight	: 0.5 kg

### GSR 3,6 V-LI BitDrive Cordless Screwdriver (0 601 9D3 0L0)



Capacity	
Max. Screw Dia.	: 5 mm
Max. Torque	: 4.5 Nm
No-load Speed	: 210 rpm
Battery Voltage	: 3.6 V / 1.5 Ah
Charger	: Micro USB
Charging Time	: 4 hours
Weight	: 0.5 kg

## 12 V Li-Ion

### GSR 12-2-LI Cordless Drill / Driver (0 601 868 1LA)

**HEAVY DUTY**  
1 year warranty\*



Capacity	
Drilling Dia.: In Steel	: 10 mm
In Wood	: 19 mm
Max. Torque	: 30 Nm
No-load Speed	: 0 - 350 / 1,300 rpm
Battery Voltage	: 12 V / 2.0 Ah
Charger	: GAL 1230 CV
Charging Time	: 35 mins
Weight	: 0.95 kg

### GSR 12 V-EC Cordless Drill / Driver (0 601 9D4 0L2)

**HEAVY DUTY**  
1 year warranty\*



Capacity	
Drilling Dia.: In Steel	: 10 mm
In Wood	: 30 mm
Max. Torque (hard/soft)	: 20 / 18 Nm
No-load Speed	: 0 - 400 / 1,300 rpm
Battery Voltage	: 12 V / 2.0 Ah
Charger	: GAL 1230 CV
Charging Time	: 45 mins
Weight	: 0.9 kg

### GSR 12 V-15 FC Cordless Drill / Driver (0 601 9F6 0L0)

**HEAVY DUTY**  
1 year warranty\*

**NEW!**



Capacity	
Drilling Dia.: In Steel	: 10 mm
In Wood	: 19 mm
Max. Torque (hard/soft)	: 30 / 15 Nm
No-load Speed	: 0 - 400 / 1,300 rpm
Battery Voltage	: 12 V / 2.0 Ah
Chuck Capacity	: 10 mm
Charging Time	: 45 mins
Charger	: AL 1230 CV
Weight	: 0.6 kg

### GDR 12 V-LI Cordless Impact Driver (0 601 9A6 9L7)

**HEAVY DUTY**  
1 year warranty\*



Capacity	
Tool Holder System	: 1/4" Hex (6.35 mm)
No-load Speed	: 0 - 2,600 rpm
Impact Rate	: 0 - 3,100 bpm
Max. Torque	: 105 Nm
Battery Voltage	: 12 V / 2.0 Ah
Charger	: AL 1230 CV
Charging Time	: 45 mins
Weight	: 0.96 kg

### GDR 12 V-EC Cordless Impact Driver (0 601 9E0 0L2)

**HEAVY DUTY**  
1 year warranty\*



Capacity	
Tool Holder System	: 1/4" Hex (6.35 mm)
No-load Speed	: 0 - 1,200 / 2,600 rpm
Impact Rate	: 0 - 2,700 / 3,100 bpm
Max. Torque	: 110 Nm
Battery Voltage	: 12 V / 2.0 Ah
Charger	: GAL 1230 CV
Charging Time	: 45 mins
Weight	: 0.95 kg

### GOP 12 V-28 (Solo)\*\* Cordless Multi-Cutter (0 601 8B5 0L0)

**HEAVY DUTY**  
1 year warranty\*

**NEW!**



Capacity	
Oscillation Angle on Left / Right	: 1.4°
No-load Speed	: 5,000 - 20,000 rpm
Weight	: 0.81 kg

### GSA 12 V-LI (Solo)\*\* Cordless Sabre Saw (0 601 64L 9L2)

**HEAVY DUTY**  
1 year warranty\*



Capacity	
Stroke speed	: 0 - 3,000 min
Stroke Length	: 14.5 mm
Pipe Diameter	: 50 mm
Wood	: 65 mm

### GST 12 V-LI (Solo)\*\* Cordless Jigsaw (0 601 5A1 0L1)

**HEAVY DUTY**  
1 year warranty\*



Capacity	
No-load Stroke Rate	: 1,500 - 2,800 rpm
Stroke Length	: 18 mm
Cutting Capacity	
- in Wood	: 70 mm
- in Aluminium	: 3 mm
- in Non-alloy Steel	: 3 mm
Weight	: 1.5 kg

### GWS 12-76 V-EC (Solo)\*\* Cordless Angle Grinder (0 601 9F2 000)

**HEAVY DUTY**  
1 year warranty\*



Capacity	
No-load Speed	: 19,500 rpm
Battery Voltage	: 12 V / 2.5 Ah
Grinding Spindle Thread	: M5
Bore Size, Diameter	: 10 mm
Weight	: 0.9 kg

### GKS 12 V-LI (Solo)\*\* Cordless Circular Saw (0 601 6A1 0L2)

**HEAVY DUTY**  
1 year warranty\*



Capacity	
No-load Speed	: 1,400 rpm
Depth of Cut - 90°	: 26.5 mm
Bore Diameter	: 15 mm
Max. Bevel	: 45°
Weight	: 1.4 kg

### GAS 12 V-LI (Solo)\*\* Cordless Vacuum Cleaner (0 601 9E3 081)

**HEAVY DUTY**  
1 year warranty\*



Capacity	
Container Volume	: 0.35 l
Filter Surface	: 408 cm²
Max. Volume Flow Rate	: 15 l/sec
Max. Volume Pressure	: 45 mbar
Weight	: 0.9 kg

## 14.4 V Li-Ion

### GDR 1440-LI Cordless Impact Driver (0 601 9B3 4L1)



Capacity	
Tool Holder System	: 1/4" Hex (6.35 mm)
No-load Speed	: 0-2,900 rpm
Impact Rate	: 0-3,200 bpm
Max. torque	: 130 Nm
Battery Voltage	: 14.4 V / 1.5 Ah
Charger	: AL 1814 CV
Charging Time	: 60 mins
Weight	: 1.2 kg

## 18 V Li-Ion

### GSB 18-2-LI Cordless Impact Drill (0 601 9D2 3L1)

**HEAVY DUTY**  
1 year warranty\*



Capacity	
Drilling Dia.: In Steel	: 10 mm
In Wood	: 30 mm
In Masonry	: 10 mm
Max. torque (hard/Soft)	: 39 / 18 Nm
Chuck Capacity	: 10 mm
Torque Settings	: 20+1
Battery Voltage	: 18 V / 2.0 Ah
Charger	: AL 1820 CV
Weight	: 1.5 kg

\* Bosch HEAVY DUTY Range Power Tools are entitled to 1 year warranty. Only Bosch Hot Air Guns, Bosch Batteries and Bosch Chargers are entitled to 6 months warranty. 1 year warranty only applicable for purchases made from 1st June 2016 onwards. Terms and Conditions apply.

\*\* Solo - Bare Tools Only, Batteries, Charger and L-BOXX to Order Separately.

18 V Li-Ion

**GDX 18 V-EC**  
Cordless Impact Wrench / Driver  
(0 601 9B9 1L0)

**HEAVY DUTY**  
1 year warranty\*



Capacity	
Tool Holder	: Hex & Square
No-load Speed	: 0 - 2,800 rpm
Impact Rate	: 0 - 3,200 bpm
Max. Torque	: 185 Nm
Battery Voltage	: 18 V / 4.0 Ah
Charger	: AL 1860 CV
Weight	: 1.7 kg

**GSR 18-2-LI (Solo)\*\***  
Cordless Drill / Driver  
(0 601 9B7 3B2)

**HEAVY DUTY**  
1 year warranty\*



Capacity	
Drilling Dia.: In Steel	: 10 mm
In Wood	: 30 mm
Max. torque (hard/soft)	: 38 / 17 Nm
Chuck Capacity	: 10 mm
No-load Speed	: 0-400 / 1,300 rpm
Torque Settings	: 20+1
Weight	: 1.3 kg

**GSR 18 V-EC (Solo)\*\***  
Cordless Drill / Driver  
(0 601 9E8 100)

**HEAVY DUTY**  
1 year warranty\*



**NEW!**



Capacity	
Drilling Dia.: In Steel	: 13 mm
In Wood	: 38 mm
Max. torque (hard/soft)	: 50 / 31 Nm
Chuck Capacity	: 13 mm
No-load Speed	: 0-600 / 1,900 rpm
Torque Settings	: 20+1
Weight	: 1.5 kg

**GSB 18 V-EC (Solo)\*\***  
Cordless Impact Drill  
(0 601 9E9 100)

**HEAVY DUTY**  
1 year warranty\*



**NEW!**



Capacity	
Drilling Dia.: In Steel	: 13 mm
In Wood	: 38 mm
In Masonry	: 13 mm
Max. torque (hard/Soft)	: 50 / 31 Nm
No-load Speed	: 0-600/1,900 rpm
Chuck Capacity	: 13 mm
Torque Settings	: 20+1
Max. Impact Rate	: 25,500 bpm
Weight	: 1.5 kg

**GDS 18 V-LI HT (Solo)\*\***  
Cordless Impact Wrench  
(0 601 9A1 3L4)

**HEAVY DUTY**  
1 year warranty\*



Capacity	
Torque Max.	: 650 Nm
No-load Speed	: 0 - 1,900 rpm
Impact Rate	: 0 - 2,100 bpm
Screw Diameter	: M12 - M20
Toolholder	: 1/2" External Square
Weight	: 3.0 kg

**GSA 18 V-LI (Solo)\*\***  
Cordless Sabre Saw  
(0 601 64J 0B1)

**HEAVY DUTY**  
1 year warranty\*



Capacity	
Stroke Length	: 28 mm
No-load Stroke	
Rate	: 0 - 2,400 / 0 - 2,700 spm
Weight	: 3.4 kg

**GSA 18 V-32 (Solo)\*\***  
Cordless Sabre Saw  
(0 601 6A8 102)

**HEAVY DUTY**  
1 year warranty\*



**NEW!**



Capacity	
Stroke Length	: 32 mm
No-load Stroke Rate	: 0 - 2,500 spm
Cutting Depth In Wood	: 230 mm
in Metal	: 175 mm
Weight	: 3.5 kg

**GST 18 V-LI B (Solo)\*\***  
Cordless Jigsaw  
(0 601 5A6 100)

**HEAVY DUTY**  
1 year warranty\*



**NEW!**

Capacity	
No-load Stroke Rate	: 0 - 2700 spm
Stroke Height	: 23 mm
Cutting Depth In Metal	: 8 mm
In Wood	: 120 mm
In Aluminium	: 120 mm
Slanted Cuts	: 0 - 45°
Weight Incl. Battery	: 2.4 kg

**GKS 18 V-57 (Solo)\*\***  
Cordless Circular Saw  
(0 601 6A2 2L0)

**HEAVY DUTY**  
1 year warranty\*

**NEW!**



Capacity	
No-load Speed	: 3,400 rpm
Blade Diameter	: 165 mm
Saw Blade Bore Diameter	: 20 mm
Max. Cutting Capacities at 90°:	57 mm
at 45°:	42 mm
Weight	: 4.1 kg

**GKM 18 V-LI (Solo)\*\***  
Cordless Metal Circular Saw  
(0 601 6A4 001)

**HEAVY DUTY**  
1 year warranty\*



Capacity	
No-load Speed	: 4,250 rpm
Blade Diameter	: 136 mm
Saw Blade Bore Diameter	: 20 mm
Cutting Capacity	: 50 mm
Battery Voltage	: 18 V
Cutting Depth Adjustment	: Yes

**GWS 18 V-LI (Solo)\*\***  
Cordless Angle Grinder  
(0 601 93A 3L5)

**HEAVY DUTY**  
1 year warranty\*



Capacity	
No-load Speed	: 10,000 rpm
Roughing/Cutting Disc,	
Diameter	: 100 mm
Weight	: 2.3 kg

**GG8 18 V-LI (Solo)\*\***  
Cordless Straight Grinder  
(0 601 9B5 300)

**HEAVY DUTY**  
1 year warranty\*



Capacity	
No-load Speed:	2 - 22,000 rpm
Toolholder	: Collet up to 8 mm Diameter
Weight	: 1.8 kg

**GAS 18 V-LI (Solo)\*\***  
Cordless Vacuum Cleaner  
(0 601 9C6 1L0)

**HEAVY DUTY**  
1 year warranty\*



Capacity	
Dust Capacity	: 700 ml
Vacuum Max.	: 4 kPa
Airflow Max.	: 19.3 l/sec
Weight	: 1.6 / 1.4 kg

**GBL 18 V-120 (Solo)\*\***  
Blower  
(0 601 9F5 1L0)

**HEAVY DUTY**  
1 year warranty\*



Capacity	
No-load Speed	: 17,000 rpm
Air Speed, Max	: 75 m/s
Air Volume	: 2.0 m³/min
Runtime	: Speed I: 9 min / Ah
Speed II:	5 min / Ah
Weight without Cable:	1.1 kg

**GCB 18 V-LI (Solo)\*\***  
Cordless Band Saw  
(0 601 2A0 300)

**HEAVY DUTY**  
1 year warranty\*



Capacity	
No-load Speed	: 162 m/min
Saw Blade Diameter:	733 x 12,7 x 0.5 mm
Max. Cutting Depth	: 63,5 mm
Weight	: 3.8 kg

**GML 18 V-LI (Solo)\*\* - Indent**  
Sound Box  
(0 601 429 970)

**HEAVY DUTY**  
1 year warranty\*



Capacity	
Music Source	: FM / AM / Aux-In
Station Presets	: 5FM / 5AM
Loudspeaker	: 2 x 5W Neodymium
Size (H x W x L)	: 148 x 110 x 307 mm
Weight	: 1.3 kg

\* Bosch HEAVY DUTY Range Power Tools are entitled to 1 year warranty. Only Bosch Hot Air Guns, Bosch Batteries and Bosch Chargers are entitled to 6 months warranty. 1 year warranty only applicable for purchases made from 1st June 2016 onwards. Terms and Conditions apply.  
\*\* Solo - Bare Tools Only, Batteries, Charger and L-BOXX to Order Separately.

## 18 V Li-Ion

**GHO 18 V-LI (Solo)\*\***  
Cordless Planer  
(0 601 5A0 300)

**HEAVY DUTY**

1 year warranty\*



Capacity	
No-load Speed	: 14.000 rpm
Cutting Depth	: 0 - 1,6 mm
Rebating Depth	: 0 - 8 mm
Planing Width, Max.	: 82 mm
Weight	: 2.6 kg

**GSS 18 V-LI (Solo)\*\***  
Cordless Orbital Sander  
(0 601 9D0 2L0)

**HEAVY DUTY**

1 year warranty\*



Capacity	
No-load Speed	: 11.000 rpm
Orbital Rate	: 22,000min-1
Orbital Diameter	: 1,6 mm
Pad Size	: 113 x 101 mm
Sanding Paper Size	: 114 x 140 mm
Weight	: 1.0 kg

**GOP 18 V-28 (Solo)\*\***  
Cordless Multi-Cutter  
(0 601 8B6 002)

**HEAVY DUTY**

1 year warranty\*

**NEW!**



Capacity	
Oscillation Angle	
Left/Right	: 1,4°
No-load Speed	: 8,000 - 20,000 rpm
Grip Circumference	: 193 mm
Tool Length (without battery)	: 312 mm
Weight	: 2.0 kg

**GBH 18 V-26 (Solo)\*\***  
Cordless Rotary Hammer **3 mode**  
(0 611 909 000)

**HEAVY DUTY**

1 year warranty\*

**NEW!**



Capacity	
In Concrete	: 4 - 26 mm
In Steel	: 13 mm
In Wood	: 30 mm
Rated Speed	: 0 - 890 rpm
Impact Rate	: 0 - 4,350 bpm
Weight	: 3.5 kg

## 36 V Li-Ion

**GBH 36 V-EC Compact**  
Cordless Rotary Hammer **2 mode**  
(0 611 903 RL1)

**HEAVY DUTY**

1 year warranty\*



Capacity	
In Concrete	: 4 - 18 mm
In Steel	: 13 mm
In Wood	: 30 mm
Rated Speed	: 0 - 1,500 rpm
Impact Rate	: 0 - 4,850 bpm
Battery Voltage	: 36 V / 2.0 Ah
Charger	: AL 3640 CV
Charging Time	: 45 mins
Weight	: 2.9 kg

**GBH 36 V-LI Plus**  
Cordless Rotary Hammer **3 mode**  
(0 611 906 0L0)

**HEAVY DUTY**

1 year warranty\*

**NEW!**



Capacity	
In Concrete	: 8 - 28 mm
In Steel	: 13 mm
In Wood	: 30 mm
Joule	: 3.2 J
Impact Rate	: 0 - 4,174 bpm
Battery Voltage	: 36 V / 4.0 Ah
Charger	: AL 3680 CV
Charging Time	: 35 mins
Weight	: 4.5 kg

## 12 V Li-Ion Battery Pack



**GBA 12 V 2.0 Ah B-0**  
(1 600 A00 F6X)



**GBA 12 V 4.0 Ah B-0**  
(1 600 A00 F7I)

## 18 V Li-Ion Battery Pack



**GBA 18 V 2.0 Ah M-B**  
(1 600 A00 1CG)



**GBA 18 V 4.0 Ah M-C**  
(1 600 A00 163)

## Charger



**GAL 1230 CV**  
(for 10.8 V & 12 V Battery)  
(1 600 A00 F6S)



**GAL 1860 CV**  
(for 14.4 V & 18 V Battery)  
(1 600 A00 16Y)

**NEW!**



**GAX 18 V-30**  
(for 12 V, 14.4 V & 18 V Battery)  
(1 600 A01 1AA)

## Starter Kit



**12 V 1.5 Ah (2 Batteries)**  
+ GAL 1230 CV (1 Charger)  
(1 600 A00 F6J)



**14.4 V 2.0 Ah (2 Batteries)**  
+ GAL 1860 CV (1 Charger)  
(1 600 A00 1AG)



**18 V 2.0 Ah (2 Batteries)**  
+ GAL 1860 CV (1 Charger)  
(1 600 A00 1AZ)



**18 V 4.0 Ah (2 Batteries)**  
+ GAL 1860 CV (1 Charger)  
(1 600 A00 1B7)

## Wireless Starter Kit



**18 V 2.0 Ah MW-B (1 Battery)**  
+ GAL 1830 W (1 Charger)  
+ Mounting Frame  
(1 600 A00 3NB)



## L-BOXX



**L-BOXX 102**  
(1 605 438 165)



**L-BOXX 136**  
(1 605 438 166)



**L-BOXX 238**  
(1 605 438 167)



**L-BOXX 374 (Indent)**  
(1 605 438 168)

## Trolley

**L-BOXX Trolley**  
(1 600 A00 1SA)

**NEW!**



**L-BOXX Roller**  
(1 6000 A00 1S9)

**NEW!**



\* Bosch HEAVY DUTY Range Power Tools are entitled to 1 year warranty. Only Bosch Hot Air Guns, Bosch Batteries and Bosch Chargers are entitled to 6 months warranty. 1 year warranty only applicable for purchases made from 1st June 2016 onwards. Terms and Conditions apply.

\*\* Solo - Bare Tools Only, Batteries, Charger and L-BOXX to Order Separately.

**Drill**

**GBM 10 RE**  
(0 601 473 5L0)

**HEAVY DUTY**  
1 year warranty\*



**Capacity**

Power Input	: 450 W
In Steel	: 10 mm
In Aluminium	: 10 mm
In Wood	: 25 mm
No-load Speed	: 0 - 2,600 rpm
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 1.3 kg

**GBM 13 RE**  
(0 601 477 5L0)

**HEAVY DUTY**  
1 year warranty\*



**Capacity**

Power Input	: 600 W
In Steel	: 13 mm
In Aluminium	: 13 mm
In Wood	: 30 mm
No-load Speed	: 0 - 2,600 rpm
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 1.65 kg

**GBM 13 HRE "High Torque"**  
(0 601 049 603)

**HEAVY DUTY**  
1 year warranty\*



**Capacity**

Power Input	: 550 W
In Steel	: 13 mm
In Aluminium	: 20 mm
In Wood	: 40 mm
No-load Speed	: 0 - 550 rpm
Torque (Approx.)	: 40 Nm
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 2.1 kg

**GBM 32-4**  
(0 601 130 203)

**HEAVY DUTY**  
1 year warranty\*



**Capacity**

Power Input	: 1,500 W
In Steel	: 32 mm
In Aluminium	: 50 / 70 mm
4 Speed	: 210 / 330 / 470 / 740 rpm
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 7.3 kg

**Impact Drill**

**GSB 10 RE**  
(0 601 216 1L6)

**HEAVY DUTY**  
1 year warranty\*



**Capacity**

Power Input	: 500 W
In Masonry	: 10 mm
In Steel	: 8 mm
In Wood	: 20 mm
No-load Speed	: 0 - 2,600 rpm
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 1.5 kg

**GSB 16 RE**  
(0 601 228 1L2)

**HEAVY DUTY**  
1 year warranty\*



**Capacity**

Power Input	: 750 W
In Concrete	: 16 mm
In Steel	: 12 mm
In Wood (hard)	: 25 mm
No-load Speed	: 0 - 3,250 rpm
Impact Rate	: 0 - 48,500 bpm
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 1.8 kg

**GSB 20-2 RE**  
(0 601 1A2 1L0)

**HEAVY DUTY**  
1 year warranty\*




**Capacity**

Power Input	: 800 W
In Concrete	: 20 mm
In Steel	: 13 mm
In Wood	: 40 mm
No-load Speed	: 0 - 1,000 / 3,000 rpm
Impact Rate	: 0 - 16,000 / 48,000 bpm
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 2.6 kg

**Multi Cutter**

**GOP 30-28**  
(0 601 237 0L0)

**HEAVY DUTY**  
1 year warranty\*



**Capacity**

Power Input	: 300W
Oscillating amplitude	: 2.8° (2 x 1.4°)
No-load Speed	: 8,000 - 20,000 opm
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 1.5 kg

**Straight Grinder**

**GG3 3000 L**  
(0 601 224 0L0)

**HEAVY DUTY**  
1 year warranty\*



**Capacity**

Power Input	: 300 W
Max. Collet Capacity	: 8 mm
No-load Speed	: 28,000 rpm
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 1.5 kg

**GG3 5000 L**  
(0 601 224 1L0)

**HEAVY DUTY**  
1 year warranty\*



**Capacity**

Power Input	: 500 W
Max. Collet Capacity	: 8 mm
No-load Speed	: 33,000 rpm
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 1.4 kg

**GG3 28 LC**  
(0 601 221 070)

**HEAVY DUTY**  
1 year warranty\*




**Capacity**

Power Input	: 650 W
Max.Collet Diameter	: 8 mm
No-load Speed	: 28,000 rpm
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 1.6 kg

**GG3 28 C**  
(0 601 220 070)

**HEAVY DUTY**  
1 year warranty\*



**Capacity**

Power Input	: 650 W
Max.Collet Diameter	: 8 mm
No-load Speed	: 28,000 rpm
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 1.4 kg

**4" Angle Grinder**

**GWS 750-100**  
(0 601 394 0L0)

**HEAVY DUTY**  
1 year warranty\*



**Capacity**

Power Input	: 750 W
No-load Speed	: 11,000 rpm
Disc Diameter	: 100 mm
Grip Size	: 59 / 54.5 mm
Perimeter	: 187 mm
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 1.8 kg

**GWS 900-100**  
(0 601 396 0L0)

**HEAVY DUTY**  
1 year warranty\*



**Capacity**

Power Input	: 900 W
Grinding / Cutting	
Disc Diameter	: 100 mm
Grinding Spindle Thread	: M10
No-load Speed	: 10,000 rpm
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 1.8 kg

**GWS 900-100 S**  
(0 601 396 1L0)

**HEAVY DUTY**  
1 year warranty\*



**Capacity**

Power Input	: 900 W
Grinding / Cutting	
Disc Diameter	: 100 mm
Grinding Spindle Thread	: M10
No-load Speed	: 10,000 rpm
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 1.9 kg

**GWS 7-100 ET**  
(0 601 388 5L0)

**HEAVY DUTY**  
1 year warranty\*



**Capacity**

Power Input	: 720 W
Grinding / Cutting	
Disc Diameter	: 100 mm
Wire Cup Brush Diameter	: 70 mm
No-load Speed	: 2,800 - 9,300 rpm
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 1.8 kg

\* Bosch HEAVY DUTY Range Power Tools are entitled to 1 year warranty. Only Bosch Hot Air Guns, Bosch Batteries and Bosch Chargers are entitled to 6 months warranty.

1 year warranty only applicable for purchases made from 1st June 2016 onwards. Terms and Conditions apply.

\*\* Solo - Bare Tools Only, Batteries, Charger and L-BOXX to Order Separately.

### 4" Angle Grinder

**GWS 8-100 Z**  
(0 601 831 5L0)



<b>Capacity</b>	
Power Input	: 800 W
Grinding / Cutting	
Disc Diameter	: 100 mm
Wire Cup Brush Diameter	: 70 mm
No-load Speed	: 11,000 rpm
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 1.9 kg

### 5" Angle Grinder

**GWS 13-125 CI**  
(0 601 79E 002)



<b>Capacity</b>	
Power Input	: 1,300 W
No-load Speed	: 11,500 rpm
Grinding Spindle Thread	: M14
Disc Diameter	: 125 mm
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 2.3 kg

### 5" Angle Grinder (Indent)

**GWS 15-125 CITH (Indent)**  
(0 601 830 E42)



<b>Capacity</b>	
Power Input	: 1,500 W
No-load Speed	: 11,500 rpm
Grinding Spindle Thread	: M14
Disc Diameter	: 125 mm
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 2.4 kg

### 5" Angle Grinder

**GWS 17-125 CI**  
(0 601 79G 002)



<b>Capacity</b>	
Power Input	: 1,700 W
No-load Speed	: 11,500 rpm
Grinding Spindle Thread	: M14
Disc Diameter	: 125 mm
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 2.4 kg

### 6" Angle Grinder

**GWS 17-150 CI**  
(0 601 79K 002)



<b>Capacity</b>	
Power Input	: 1,700 W
No-load Speed	: 11,500 rpm
Grinding Spindle Thread	: M14
Disc Diameter	: 150 mm
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 2.4 kg

### 7" Angle Grinder

**GWS 20-180**  
(0 601 849 106)



<b>Capacity</b>	
Power Input	: 2,000 W
No-load Speed	: 8,500 rpm
Grinding / Cutting	
Disc Diameter	: 180 mm
Wire Cup Brush Diameter	: 100 mm
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 4.2 kg

### 9" Angle Grinder

**GWS 20-230**  
(0 601 850 106)



<b>Capacity</b>	
Power Input	: 2,000 W
Grinding / Cutting	
Disc Diameter	: 230 mm
Wire Cup Brush Diameter	: 100 mm
No-load Speed	: 6,500 rpm
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 5.6 kg

### Stirrer / Mixer Drill

**GRW 12 E**  
(0 601 1A7 070)



<b>Capacity</b>	
Power Input	: 1,200 W
Connector Type	: M14 Inside Thread
Max. Paddle Ø	: 140 mm
Incl. Paddle Ø	: 140 mm
No-load Speed	: 0 - 1,000 rpm
Nominal speed	: 0 - 620 min <sup>-1</sup>
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 5.3 kg

### Bench Grinder

**GBG 35-15**  
(0 601 27A 3L0)



<b>Capacity</b>	
Power Input	: 350 W
No-load Speed	: 3,000 rpm
Disc Diameter	: 150 mm
Weight	: 10 kg

**GBG 60-20**  
(0 601 27A 4L0)



<b>Capacity</b>	
Power Input	: 600 W
No-load Speed	: 3,800 rpm
Disc Diameter	: 200 mm
Weight	: 17 kg

### Screwdriver

**GSR 6-25 TE**  
(0 601 445 0P0)



<b>Capacity</b>	
Power Input	: 701 W
Self-tapping Screws	
Diameter	: 6 mm
No-load Speed	: 0 - 2,500 rpm
Max. torque	: 20 Nm
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 1.5 kg

**GSR 6-45 TE**  
(0 601 445 1P0)



<b>Capacity</b>	
Power Input	: 701 W
Self-tapping Screws	
Diameter	: 6 mm
No-load Speed	: 0 - 4,500 rpm
Max. torque	: 12 Nm
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 1.4 kg

### Shear

**GSC 2.8**  
(0 601 506 142)



<b>Capacity</b>	
Power Input	: 500 W
In Steel	: 2.8 mm
In Aluminium	: 3.5 mm
No-load Stroke Rate	: 2,400 stroke/min
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 2.7 kg

### Jigsaw

**GST 65**  
(0 601 509 1L0)



<b>Capacity</b>	
Power Input	: 400 W
In Wood	: 65 mm
In Metal	: 3 mm
No-load Stroke Rate	: 3,100 spm
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 1.7 kg

### Jigsaw

**GST 80 PBE**  
(0 601 581 59F)



<b>Capacity</b>	
Power Input	: 580 W
In Wood	: 85 mm
In Metal	: 10 mm
No-load Stroke Rate	: 500 - 3,100 spm
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 2.4 kg

### Jigsaw

**GST 25 M**  
(0 601 516 0L0)



<b>Capacity</b>	
Power Input	: 670 W
In Wood	: 80 mm
In Aluminium	: 25 mm
In Steel	: 15 mm
No-load Speed	: 500 - 2,600 rpm
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 2.7 kg

### Nibbler

**GNA 2.0**  
(0 601 530 103)

**HEAVY DUTY** 1 year warranty



1 607 031 228

Capacity	
Power Input	: 500 W
Mild Steel	: 2.0 mm
Stainless Steel	: 1.0 mm
No-load Stroke Rate	: 2,400 stroke/min
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 2.0 kg

### Sabre Saw

**GSA 1100 E**  
(0 601 64C 8L0)

**HEAVY DUTY** 1 year warranty



1 610 956 917

Capacity	
Power Input	: 1,100 W
Cutting depth: In Wood	: 230 mm
In Metal	: 20 mm
No-load Stroke Rate	: 2,700 stroke/min
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 3.6 kg

### Diamond Wheel Cutter

**GDM 13-34**  
(0 601 36A 2L0)

**HEAVY DUTY** 1 year warranty



1 619 P06 304

Capacity	
Power Input	: 1,300 W
Blade Diameter	: 110 mm
Max. Cutting Depth	: 34 mm
Base Plate	: 100 x 190 mm
No-load Speed	: 12,000 rpm
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 2.8 kg

### Foam Cutter

**GSG 300**  
(0 601 575 103)

**HEAVY DUTY** 1 year warranty



2 604 320 911

Capacity	
Power Input	: 350 W
Cutting Capacity	: 300 mm
No-load Stroke Rate	: 3,200 spm
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 1.6 kg

### Circular Saw

**GKS 66 X**  
(0 601 676 1L0)

**HEAVY DUTY** 1 year warranty



1 619 P10 063

Capacity	
Power Input	: 1,200 W
Cutting Depth at 90°	: 66 mm
at 45°	: 47 mm
No-load Speed	: 4,900 rpm
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 3.4 kg

**GKS 190**  
(0 601 623 0L0)

**HEAVY DUTY** 1 year warranty



1 619 P06 346

Capacity	
Power Input	: 1,400 W
Blade Diameter	: 184 mm
Max. Cutting Capacities at 90°	: 67 mm
at 45°	: 48 mm
No-load Speed	: 5,500 rpm
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 4.1 kg

**GKS 235 Turbo**  
(0 601 5A2 0L0)

**HEAVY DUTY** 1 year warranty



1 619 P01 685

Capacity	
Power Input	: 2,050 W
Saw Blade Diameter	: 235 mm
Max. Cutting Capacities at 90°	: 85 mm
at 45°	: 65 mm
No-load Speed	: 0 - 5,300 rpm
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 7.6 kg

### Cut-off Machine

**GCO 14-24 J**  
(0 601 B37 2L0)

**HEAVY DUTY** 1 year warranty



1 607 014 171

Capacity	
Power Input	: 2,400 W
Saw Blade Diameter	: 355 mm
Saw Blade Bore	: 25.4 mm
No-load Speed	: 3,800 rpm
Cutting Capacity	: 100 x 196 mm
	: 119 x 119 mm
	: 130 x 130 mm
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 18.1 kg

### Mitre Saw

**GCM 10 MX**  
(0 601 B29 0L0)

**HEAVY DUTY** 1 year warranty



1 607 014 171

Capacity	
Power Input	: 1,700 W
Blade Size	: 255 mm
Arbour Size	: 25.4 mm
No-load Speed	: 4,800 rpm
Max Mitre	: 45° L / 52° R
Max. Cutting Capacity	: 89 x 89 mm
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 13.5 kg

**GCM 12 GDL**  
(0 601 B23 670)

**HEAVY DUTY** 1 year warranty



2 610 021 311

Capacity	
Power Input	: 2,000 W
Blade Size	: 305 mm
Arbour Size	: 30 mm
No-load Speed	: 3,800 rpm
Max. Mitre	: 52° L / 60° R
Cutting Capacity	: 104 x 341 mm
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 32.1 kg

### Slide Mitre Saw

**GCM 8 SJL**  
(0 601 B19 1L0)

**HEAVY DUTY** 1 year warranty



1 609 B03 790

Capacity	
Power Input	: 1,600 W
Blade Size	: 216 mm
Bore Size	: 30 mm
No-load Speed	: 5,500 rpm
Max. Miter	: 52° L / 60° R
Cutting Capacity	: 70 x 312 mm
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 17.3 kg

### Mitre Saw Stand

**T1B**  
(0 601 B12 310)



Capacity	
Length of Work Bench without Extension	: 1,220 mm
Length of Work Bench with extension	: 2,630 mm
Weight	: 15 kg / 19 kg

### Table Saw

**GTS 10 J**  
(0 601 B30 5L0)

**HEAVY DUTY** 1 year warranty



2 610 018 332

Capacity	
Power Input	: 1,800 W
Saw Blade Diameter	: 254 mm
Bevel Setting	: 47° L / 2° R
Cutting Capacity (right)	: 460 mm
(Left)	: 210 mm
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 26 kg

### Table Saw Stand

**GTA 600**  
(0 601 B22 002)



Capacity	
Table Height	: 602 mm
Max. Length Extension	
Unfolded	: 450 x 520 (D x L)
Max. Load Capacity	: 60 kg
Weight	: 6.3 kg

### Planer

**GHO 10-82**  
(0 601 594 006)

**HEAVY DUTY** 1 year warranty



2 609 120 064

Capacity	
Power Input	: 710 W
Planing Width	: 82 mm
Planing Depth	: 0 - 3.0 mm
No-load Speed	: 16,500 rpm
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 2.5 kg

### Eccentric Sander

**GEX 125-1 A / GEX 125-1 AE**  
(0 601 387 0L0) / (0 601 387 5L0)

**HEAVY DUTY** 1 year warranty



2 609 120 199

Capacity	
Power Input	: 250 W
No-load Speed	: 7,500 - 12,000 rpm
Oscillating Circuit	
Diameter	: 2.5 mm
Orbit Rate	: 15,000 - 24,000 opm
Sanding Plate	: 125 mm
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 1.3 kg

\* Bosch HEAVY DUTY Range Power Tools are entitled to 1 year warranty. Only Bosch Hot Air Guns, Bosch Batteries and Bosch Chargers are entitled to 6 months warranty. 1 year warranty only applicable for purchases made from 1st June 2016 onwards. Terms and Conditions apply.

**Orbital Sander** **Belt Sander**

**GSS 1400**  
(0 601 2A2 0L0)



2 609 120 199

Capacity	
Power Input	: 180 W
No-load Speed	: 12,000 rpm
Orbital Rate	: 24,000 opm
Oscillating Circuit Dia.	: 1.6 mm
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 1.4 kg

**GSS 230**  
(0 601 070 0L0)



2 609 120 199

Capacity	
Power Input	: 350 W
No-load Speed	: 12,000 rpm
Orbit Rate	: 24,000 opm
Sand Paper Size	: 92 x 182 mm
Clamping Velcro	: 93 x 230 mm
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 1.4 kg

**GSS 280 AVE (Indent)**  
(0 601 292 971)



1 607 031 234

Capacity	
Power Input	: 350 W
No-load Speed	: 12,000 rpm
Orbit Rate	: 24,000 opm
Sand Paper Size	: 92 x 182 mm
Clamping Velcro	: 93 x 230 mm
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 1.4 kg

**GBS 75 A**  
(0 601 274 004)



1 607 031 222

Capacity	
Power Input	: 710 W
No-load Belt Speed	: 300 m/min
Sanding Surface	: 75 x 130 mm
Belt Size	: 75 x 533 mm
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 3.2 kg

**Polisher**

**GPO 12 CE**  
(0 601 389 0L0)



1 607 014 176

Capacity	
Power Input	: 1,250 W
No-load Speed	: 750 - 3,000 rpm
Polishing Disc Diameter	: 180 mm
Thread of Polishing Spindle	: M14
Tool Length	: 450 mm
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 2.5 kg

**Mini Router / Trimmer**

**GMR 1**  
(0 601 60A 0L0)



2 609 120 149

Capacity	
Power Input	: 550 W
Collet	: 6 mm or 1/4"
No-load Speed	: 33,000 rpm
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 1.5 kg

**Router**

**GOF 1600 CE**  
(0 601 624 0L0)



2 610 007 957

Capacity	
Power Input	: 1,600 W
Toolholder	: 8 - 12,7 mm
No-load Speed	: 10,000 - 25,000 rpm
Max. Router Cage Stroke	: 76 mm
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 5.8 kg

**Blower**

**GBL 800 E**  
(0 601 980 4L0)



1 604 321 129

Capacity	
Power Input	: 800 W
No-load Speed	: 16,000 rpm
Air Volume	: 4.5 m³/min
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 1.8 kg

**Hot Air Gun**

**GHG 600-3**  
(0 601 94B 006)



6 months warranty

Capacity	
Power Input	: 1,800 W
Temperature	: 50 / 400 / 600°C
Air Flow	: 250 / 350 / 500 l/min
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 0.8 kg

**GHG 630 DCE**  
(0 601 94C 706)



6 months warranty

Capacity	
Power Input	: 2,000 W
Temperature	: 50 - 630°C
Air Flow	: 150 / 300 / 500 l/min
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 0.9 kg

**Wet & Dry Vacuum Cleaner**

**GAS 11-21**  
(0 601 97A 006)



1 year warranty

Capacity	
Power Input	: 1,100 W
Container Volume	: 21 litre
Air Flow Max.	: 50 l/sec
Volume	: 150 mbar
Hose Diameter	: 35 mm
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 6.3 kg

**GAS 15 PS**  
(0 601 9E5 1L0)



NEW!

Capacity	
Power Input	: 1,100 W
Container (gross/net)	: 15 / 8 litre
Air Flow Max.	: 33 l/sec
Max. Vacuum Pressure	: 22 kPa
Weight	: 6 kg
- Semi-automatic filter cleaning system, - 2 in 1: vacuuming and blowing	

**Glue Gun**

**GKP 200 CE**  
(0 601 950 703)



1 year warranty

Capacity	
Gluing Capacity	: 30 g/min
No. of Heating Elements	: 2
Warming Up Time	: 4 min
Glue Stick Length	: 200 mm
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 0.4 kg

**High Pressure Washer (Industrial Applications)**

**GHP 5-13 C**  
(0 600 910 0L0)



Capacity	
Motor Power	: 2,300 W
Maximum Pressure	: 140 Bar
Maximum Flow Rate	: 520 l/h
Hose Length	: 8 m
Voltage	: 220 -240 V
Frequency	: 50 Hz
Weight	: 16.5 kg

**GHP 5-65**  
(0 600 910 5L0)



Capacity	
Motor Power	: 2,400 W
Maximum Pressure	: 160 Bar
Maximum Flow Rate	: 520 l/h
Hose Length	: 10 m
Voltage	: 220 -240 V
Frequency	: 50 Hz
Weight	: 24 kg

**GHP 5-75 X**  
(0 600 910 8L0)



Capacity	
Motor Power	: 2,600 W
Maximum Pressure	: 185 Bar
Maximum Flow Rate	: 570 l/h
Hose Length	: 10 m
Voltage	: 220 -240 V
Frequency	: 50 Hz
Weight	: 27 kg

\* Bosch HEAVY DUTY Range Power Tools are entitled to 1 year warranty. Only Bosch Hot Air Guns, Bosch Batteries and Bosch Chargers are entitled to 6 months warranty. 1 year warranty only applicable for purchases made from 1st June 2016 onwards. Terms and Conditions apply.

## Rotary Hammer

**GBH 2-23 REA**  
(0 611 250 570)



Capacity	
Power Input	: 710 W
In Concrete	: 4 - 23 mm
In Steel	: 13 mm
In Wood	: 30 mm
No-load Speed	: 0 - 1,000 rpm
Impact Rate	: 0 - 4,400 bpm
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight Without Dust Extraction	: 2.9 kg
Weight With Dust Extraction	: 3.6 kg

**GBH 2-24 DRE**  
(0 611 272 1L4)



Capacity	
Power Input	: 790 W
In Concrete	: 4 - 24 mm
In Steel	: 13 mm
In Wood	: 30 mm
No-load Speed	: 0 - 920 rpm
Impact Rate	: 0 - 4,100 bpm
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 2.8 kg

**GBH 2-26 DRE**  
(0 611 253 76C)



Capacity	
Power Input	: 800 W
In Concrete	: 4 - 26 mm
In Steel	: 13 mm
In Wood	: 30 mm
No-load Speed	: 0 - 900 rpm
Impact Rate	: 0 - 4,000 bpm
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 2.7 kg

**GBH 2-26 DFR**  
(0 611 254 76C)



Capacity	
Power Input	: 800 W
In Concrete	: 4 - 26 mm
In Steel	: 13 mm
In Wood	: 30 mm
No-load Speed	: 0 - 900 rpm
Impact Rate	: 0 - 4,000 bpm
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 2.9 kg

**GBH 2-28 DFV**  
(0 611 267 2L1)



Capacity	
Power Input	: 820 W
Impact Energy	: 3.2 J
In Concrete	: 4 - 28 mm
In Steel	: 13 mm
In Wood	: 30 mm
No-load Speed	: 0 - 1,300 rpm
Impact Rate	: 0 - 5,100 bpm
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 3.1 kg

**GBH 3-28 DFR**  
(0 611 244 0L0)



Capacity	
Power Input	: 800 W
In Concrete	: 28 mm
In Steel	: 13 mm
In Wood	: 30 mm
No-load Speed	: 0 - 900 rpm
Impact Rate	: 0 - 4,000 bpm
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 3.6 kg

**GBH 4-32 DFR**  
(0 611 332 1L0)



Capacity	
Power Input	: 900 W
In Concrete	: 32 mm
In Steel	: 13 mm
In Wood	: 32 mm
No-load Speed	: 0-760 rpm
Impact Rate	: 0-3,600 bpm
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 4.7 kg

## Rotary Hammer with SDS-Max

**GBH 5-40 D**  
(0 611 269 0L0)



Capacity	
Power Input	: 1,100 W
Impact Energy (EPTA)	: 8.5 J
Max. App. in core cutter	: 90 mm
No-load Speed	: 170 - 340 rpm
Impact Rate	: 1,510 - 2,900 bpm
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 6.8 kg

**GBH 5-40 DCE**  
(0 611 264 070)



Capacity	
Power Input	: 1,150 W
Impact Energy	: 2-11 J
Impact Rate	: 1,500-3,050 bpm
No-load Speed	: 170-340 rpm
Drilling Dia Concrete	: 12-40 mm
Vibration Values Drilling /Chiselling	: 10.5 / 7 / 5 m/s <sup>2</sup>
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 6.8 kg

**GBH 8-45 D**  
(0 611 265 1L0)



Capacity	
Power Input	: 1500 W
Impact Rate	: 1,380 - 2,760 bpm
Impact Energy	: 12.5 J
Rated Speed	: 150 - 305 rpm
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 8.5 kg

**GBH 8-45 DV**  
(0 611 265 0L0)



Capacity	
Power Input	: 1500 W
Impact Rate	: 1,380 - 2,760 bpm
Impact Energy	: 12.5 J
Drilling Dia Concrete	: 12 mm - 45 mm
Vibration Values	
Drilling / Chiselling	: 8/7 m/s <sup>2</sup>
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 8.5 kg

## Demolition Hammer

**GSH 3 E**  
(0 611 320 703)



Capacity	
Power Input	: 650 W
Impact Rate	: 0-3,500 bpm
Impact Force	: 4.3 J
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 3.5 kg

**GSH 5 (MAX)**  
(0 611 337 0L0)



Capacity	
Power Input	: 1,100 W
Impact rate	: 2,850 bpm
Impact Energy	: 7.5 J
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 5.6 kg

**GSH 5 CE**  
(0 611 321 0L0)



Capacity	
Power Input	: 1,150 W
Impact Rate	: 1,300 - 2,900 bpm
Impact Force	: 2 - 13 J
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 6.2 kg

**GSH 9 VC**  
(0 611 322 0L0)



Capacity	
Power Input	: 1,500 W
Impact Force	: 13 J
Vibration Value	: 9.5 m/s <sup>2</sup>
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 8.5 kg

**GSH 11 E**  
(0 611 316 706)



Capacity	
Power Input	: 1,500 W
Impact Rate	: 900 - 1,890 bpm
Impact Force	: 6 - 25 J
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 10.1 kg

\* Bosch HEAVY DUTY Range Power Tools are entitled to 1 year warranty. Only Bosch Hot Air Guns, Bosch Batteries and Bosch Chargers are entitled to 6 months warranty. 1 year warranty only applicable for purchases made from 1st June 2016 onwards. Terms and Conditions apply.




## Demolition Hammer

**GSH 11 VC**  
(0 611 336 0L0)

**HEAVY DUTY**

1 year warranty



Capacity	
Power Input	: 1,700 W
Impact Rate	: 900 - 1,700 bpm
Impact Force	: 23 J
Vibration Values Chiselling:	8 m/s <sup>2</sup>
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 11.4 kg

**GSH 16-30**  
(0 611 335 1L0)

**HEAVY DUTY**

1 year warranty



Capacity	
Power Input	: 1,750 W
Impact Rate	: 1,300 bpm
Impact Force	: 45 J
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 16.5 kg

**GSH 27 VC**  
(0 611 30A 070)

**HEAVY DUTY**

1 year warranty














Capacity	
Power Input	: 2,000 W
Impact Rate	: 1,000 bpm
Impact Force	: 69 J
Vibration Values Chiselling:	8.5 m/s <sup>2</sup>
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 29.5 kg

# Rotary Hammers application overview

Masonry: ■ Optimal ■ Total range of all application














Concrete: ■ Optimal ■ Total range of all application

Products		Drilling diameter in concrete, masonry (mm)																				Drilling in wood (mm)				Drilling in steel (mm)				
		4	6	8	10	12	14	16	18	20	22	24	26	28	30	32	34	36	38	40	42	44	46	48	50	52	up to 20	20-25	25-30	30-40
2 kg Hammers	 <b>GBH 2-24 DRE Professional</b>	[Masonry: 4-24mm Total range, 4-24mm Optimal]																				[Wood: 20-30mm Total range]				[Steel: 10-13mm Optimal]				
	 <b>GBH 2-26 DRE Professional</b>	[Masonry: 4-26mm Total range, 4-26mm Optimal]																				[Wood: 20-30mm Total range]				[Steel: 10-13mm Optimal]				
	 <b>GBH 2-26 DFR Professional</b>	[Masonry: 4-26mm Total range, 4-26mm Optimal]																				[Wood: 20-30mm Total range]				[Steel: 10-13mm Optimal]				
	 <b>GBH 2-28 DFV Professional</b>	[Masonry: 4-28mm Total range, 4-28mm Optimal]																				[Wood: 20-30mm Total range]				[Steel: 10-13mm Optimal]				
2 kg Cordless Hammers	 <b>GBH 18 V-26 Professional</b>	[Masonry: 4-26mm Total range, 4-26mm Optimal]																				[Wood: 20-30mm Total range]				[Steel: 10-13mm Optimal]				
	 <b>GBH 36 V-LI PLUS Professional</b>	[Masonry: 4-26mm Total range, 4-26mm Optimal]																				[Wood: 20-30mm Total range]				[Steel: 10-13mm Optimal]				
	 <b>GBH 36 V-LI Compact Professional</b>	[Masonry: 4-18mm Total range, 4-18mm Optimal]																				[Wood: 20-30mm Total range]				[Steel: 10-13mm Optimal]				
3 kg Hammer	 <b>GBH 3-28 DFR Professional</b>	[Masonry: 4-28mm Total range, 4-28mm Optimal]																				[Wood: 20-30mm Total range]				[Steel: 10-13mm Optimal]				
4 kg Hammer	 <b>GBH 4-32 DFR Professional</b>	[Masonry: 4-32mm Total range, 4-32mm Optimal]																				[Wood: 20-30mm Total range]				[Steel: 10-13mm Optimal]				
5 kg Hammer	 <b>GBH 5-40 DCE Professional</b>	[Masonry: 12-40mm Total range, 12-40mm Optimal]																				[Wood: 20-30mm Total range]				[Steel: 10-13mm Optimal]				
8 kg Hammer	 <b>GBH 8-45 D / DV Professional</b>	[Masonry: 12-45mm Total range, 12-45mm Optimal]																				[Wood: 20-30mm Total range]				[Steel: 10-13mm Optimal]				

■ Optimal ■ Possible

■ Optimal ■ Possible

● Drilling ● Chiselling

Drilling with hole saws in wood (mm)				Core cutting application in masonry, concrete (mm)				Material for drilling						Other characteristics		
up to 30	30-40	40-50	50-70	40-68	68-82	82-90	90-150	Reinforced concrete, granite, stone	Concrete	Bricks, hollow blocks	Hard wood	Soft wood	Metal	Drilling/ Chiselling ratio	Working direction	Special features
■	■			■				■	■	■	■	■	■	● 90% ● 10%	↕	
■	■	■		■				■	■	■	■	■	■	● 90% ● 10%	↕	
■	■	■		■				■	■	■	■	■	■	● 90% ● 10%	↕	Quick change chuck
■	■	■		■	■			■	■	■	■	■	■	● 90% ● 10%	↕	Quick change chuck 
■	■	■		■				■	■	■	■	■	■	● 90% ● 10%	↕	  
■	■	■		■				■	■	■	■	■	■	● 90% ● 10%	↕	 
■	■	■		■				■	■	■	■	■	■	● 100%	↕	  
■	■	■		■	■			■	■	■	■	■	■	● 80% ● 20%	↕	Quick change chuck 
■	■	■		■	■	■		■	■	■	■	■	■	● 70% ● 30%	↕	Quick change chuck 
				■	■	■		■	■	■				● 60% ● 40%	↕	
				■	■	■	■	■	■	■				● 50% ● 50%	↕	 Anti Vibration for GBH 8-45 DV only

# Demolition Hammers application overview

■ Optimal ■ Possible

		Specification								
		Power	Weight	Impact energy	Tool holder	Working direction	Wall tile removal	Floor tile removal	Joint repair (removal of excess concrete)	De-plastering (removing cement plaster from the walls)
		650 W	3.5 kg	4.3 J			■	■	■	■
		1100 W	5.6 kg	7.5 J			■	■	■	■
		1025 W	5.5 kg	6.8 J	17 mm Hex		■	■	■	■
		1150 W	6.2 kg	2-13 J			■	■	■	■
		1500 W	8.5 kg	13 J			■	■	■	■
		1500 W	10.1 kg	6-25 J				■	■	■
		1700 W	11.4 kg	23 J				■	■	■
		1750 W	16.7 kg	45 J	30 mm Hex					
		2000 W	29.5 kg	69 J	28 mm Hex					
Accessories		Pointed chisel	SDS plus/SDS max/Hex 17/Hex 28/Hex 30				■	■	■	■
		Flat chisel	SDS plus/SDS max/Hex 17/Hex 28/Hex 30				■	■	■	
		Tile chisel	SDS plus/SDS max				■	■		
		Spade chisel	SDS plus/SDS max/Hex 28/Hex 30				■	■	■	■
		Gouging chisel	SDS plus/SDS max							
		Bush hammer head	SDS max							
		Asphalt cutter	SDS max							
		Tamping plate	SDS max/Hex 28/Hex 30							
	Excavation chisel	SDS max/Hex 30								

Application										
Roughing of concrete walls, columns	Wall chasing or groove cutting on masonry, cement blocks, concrete walls	Concrete wall corrections	Column & beam corrections (removing bulge, exposing reinforcements)	Making cut outs or breaches in masonry wall	Hacking of concrete & masonry walls (heavy duty)	Demolition of concrete floor, slabs	Foundation breaking, pavement breaking	Road works (Restoration of Asphalt coverings)	Digging in hard compacted soil	Compacting earth & gravel
	■									
■	■	■	■	■	■					
■	■	■	■	■	■					
■	■	■	■	■	■					
■	■	■	■	■	■					
■			■	■	■	■	■	■		
■			■	■	■	■	■	■		
						■	■	■	■	■
		■	■	■	■	■	■	■		
	■	■	■	■	■	■	■	■	■	
■	■									
								■		
										■
									■	

# 18V Cordless

GSB 180-LI  
Cordless Impact Drill  
(0 601 9F8 3L0)

NEW! RSP:  
**RM549\***



Capacity	
Battery Voltage	: 18 V / 1.5 Ah
Chuck Capacity	: 13 mm
Torque (Hard / Soft)	: 54/ 21 Nm
No-load Speed (1st / 2nd gear)	: 0 - 450 / 0 - 1,700 rpm
Impact Rate	: 0 - 27,000 min
Max Screw Dia.	: 10 mm
Max Drilling Wood / Steel / Masonry	: 35 mm / 10 mm / 8 mm
Charger	: AL 1814 CV

GBH 180-LI (3 Mode)  
Cordless Rotary Hammer  
(0 611 911 0L2)

NEW! RSP:  
**RM999\***



Capacity	
Impact Force	: 1.7 J
No-load Speed	: 0 - 1,800 rpm
Impact Rate	: 0 - 4,550 bpm
Drilling Capacity Concrete	: 20 mm
Battery Voltage	: 18 V / 3.0 Ah
Charger	: AL 1820 CV
Weight	: 2.6 kg

GDS 250-LI  
Cordless Impact Wrench  
(0 611 9G6 1L0)

NEW! RSP:  
**RM619\***



Capacity	
Battery Voltage	: 18 V / 3.0 Ah
Charger	: AL 1820 CV
Max Torque	: 250 Nm
No-load Speed	: 0 - 2,400 1/min
Impact Rate	: 0 - 33,000 bpm
Tool Holder	: 1/2" Square (Pin Hole + Retention Ring)
Screw Size	: M10 - M18

GLI 180-LI (Solo)\*\*  
Cordless Worklight  
(0 601 4A1 1L0)

NEW! RSP:  
**RM129\***



Capacity	
Voltage	: 18 V
Brightness in Lumen	: 300 Lm
No. of LED	: 6 Qnt
Runtime	: 300 min / Ah
Dimensions	: 116 x 78 x 163 mm
Weight	: 0.30 kg

GSR 180-LI  
Cordless Drill / Driver  
(0 601 9F8 1L0)

RSP:  
**RM499\***



Capacity	
Battery Voltage	: 18 V / 1.5 Ah
Chuck Capacity	: 13 mm
Clutch Setting	: 20 + 1
No-load Speed (1st/2nd gear)	: 0 - 450 rpm/0 - 1,700 rpm
Torque Settings	: 20+1
Max Screw Dia.	: 10 mm
Max Drilling Wood / Steel	: 35 / 10 mm
Weight	: 1.0 kg

# 12V Cordless

GSR 120-LI  
Cordless Drill / Driver  
(0 601 9F7 0L0)

RSP:  
**RM339\***



Capacity	
Battery Voltage	: 12 V / 1.5 Ah
Chuck Capacity	: 0.8 - 10 mm
Clutch Setting	: 15 + 1
No-load Speed (1st gear)	: 0 - 430 rpm
(2nd gear)	: 0 - 1,600 rpm
Max. Torque (Hard / Soft)	: 28 / 11 Nm
Max Screw Dia.	: 7 mm
Max Drilling Wood / Steel	: 19 / 6 mm
Weight	: 1.0 kg

GSB 120-LI  
Cordless Impact Drill  
(0 601 9F3 0L3)

RSP:  
**RM379\***



Capacity	
Battery Voltage	: 10.8 V / 1.5 Ah
Max. Torque (Hard / Soft)	: 28 / 11 Nm
No-load Speed	: 0 - 400 / 1,300 rpm
Impact Rate	: 18,750 bpm
Max Screw Dia.	: 7 mm
Chuck Capacity	: 10 mm
Weight	: 1.1 kg

GDR 120-LI  
Cordless Impact Driver  
(0 601 9F0 0L1)

RSP:  
**RM429\***



Capacity	
Battery Voltage	: 12 V / 1.5 Ah
Max. Torque Hard	: 100 Nm
No-load Speed	: 0 - 1,300 / 1,600 rpm
Impact Rate	: 2,800 - 3,400 bpm
Max Screw Dia.	: 7 mm
Bit Holder	: 1/4"
Charging Time	: 90 mins
Weight	: 1.05 kg

\* Recommended Selling Prices (RSP) and Spare Part Prices are inclusive 6% GST. Subject to change without prior notice. Valid in West Malaysia and while stocks last only.

\*\* Solo - Bare Tools Only, Batteries, Charger and L-BOXX to Order Separately.

**GKS 600**  
Circular Saw  
(0 601 6A9 0L0)

**NEW!**

RSP:  
**RM429\***



Capacity	
Power Input	: 1,200 W
No-load Speed	: 5,000 rpm
Blade Bore Size	: 20 mm
Disc Diameter	: 165 mm
Cutting depth (90°/45°)	: 55 / 37 mm
Weight	: 1.6 kg

**GKS 7000**  
Circular Saw  
(0 601 676 0L0)

RSP:  
**RM399\***



Capacity	
Power Input	: 1,100 W
Saw Blade Diameter	: 184 mm
Cutting Depth (90°)	: 65 mm
Cutting Depth (45°)	: 47 mm
No-load Speed	: 5,200 rpm
Weight	: 3.6 kg

**GSH 500**  
Demolition Hammer  
(0 611 338 5L0)



RSP:  
**RM699\***



Capacity	
Power Input	: 1,025 W
Impact Rate	: 2,750 bpm
Impact Energy	: 6.8 J
No-load Speed	: 2,800 rpm
Weight	: 5.5 kg

**GHO 6500**  
Planer  
(0 601 596 0L0)

RSP:  
**RM299\***



Capacity	
Power Input	: 650 W
No-load Speed	: 16,500 rpm
Adjustable Chip Thickness	: 0 - 2.6 mm
Adjustable Rebating Depth	: 0 - 9 mm
Weight	: 2.8 kg

**GWS 060**  
Angle Grinder  
(0 601 375 6L0)

RSP:  
**RM129\***



Capacity	
Power Input	: 670 W
No-load Speed	: 12,000 rpm
Grinding Spindle Thread	: M10
Disc Diameter	: 100 mm
Weight	: 1.6 kg

**GBM 320**  
Drill  
(0 601 1A4 5L0)

RSP:  
**RM159\***



Capacity	
Power Input	: 320 W
In Steel	: 6.5 mm
In Aluminium	: 13 mm
In Wood	: 6.5 mm
No-load Speed	: 4,200 rpm
Weight	: 1.0 kg

**GBM 350**  
Drill  
(0 601 1A9 5L0)

RSP:  
**RM149\***



Capacity	
Power Input	: 350 W
In Steel	: 10 mm
In Wood	: 20 mm
No-load Speed	: 2,800 rpm
Weight	: 1.2 kg

**GDM 121**  
Diamond Cutter  
(0 601 395 0L0)

RSP:  
**RM259\***



Capacity	
Power Input	: 1,250 W
No-load Speed	: 14,500 rpm
Cutting Depth (at 90°)	: 34 / 36 mm
Cord Length (rubber)	: 2.1 m
Weight	: 2.8 kg

**GCO 200**  
Cut-Off Saw  
(0 601 B37 0L0)

RSP:  
**RM499\***



Capacity	
Power Input	: 2,000 W
Cutting Capacity 0°	: 119 x 119 mm
	: 129 mm
	: 100 x 196 mm
	: 130 x 130 mm
Saw Blade Bore	: 25.4 mm
Saw Blade Diameter	: 355 mm
No-load Speed	: 3,800 rpm
Weight	: 17 kg

\* Recommended Selling Prices (RSP) and Spare Part Prices are inclusive 6% GST. Subject to change without prior notice. Valid in West Malaysia and while stocks last only.

## Laser Rangefinder

**GLM 30**  
(0 601 072 5K0)



Capacity	
Laser Diode	: 635 nm, <1mW
Measuring Range*	: 0.15 - 30 m
Measuring Accuracy	: ± 2.0 mm
Measuring Units	: m / ft
Batteries	: 2 x 1.5 V LR03(AAA)
Weight	: 0.1 kg

**GLM 40**  
(0 601 072 9K0)



Capacity	
Laser Diode	: 635 nm, <1mW
Measuring Range*	: 0.15 - 40 m
Measuring Accuracy	: ± 2.0 mm
Measuring Units	: m / ft
Batteries	: 2 x 1.5 V LR03(AAA)
Weight	: 0.1 kg

**GLM 500**  
(0 601 072 HK0)

NEW!



Capacity	
Laser Diode	: 635 nm, <1mW
Measuring Range*	: 0.05 - 500 m
Measuring Accuracy	: ± 1.5 mm
Measuring Units	: m, cm, ft, in
Batteries	: 4 x 1.5 V LR03(AAA)
Weight	: 0.1 kg

**GLM 50 C**  
(0 601 072 CK0)



Capacity	
Laser Diode	: 635 nm, <1mW
Measuring Range*	: 0.05 - 50 m
Measuring Accuracy	: ± 1.5 mm
Measuring Units	: m, ft, in
Batteries	: 2 x 1.5 V LR03(AAA)
Weight	: 0.1 kg

**GLM 80**  
(0 601 072 370)



Capacity	
Laser Diode	: 635 nm, <1mW
Measuring Range*	: 0.05 - 80 m
Measuring Accuracy	: ± 1.5mm
Measuring Units	: mm, cm, m, ft, in
Batteries	: Lithium-Ion
Weight	: 0.14 kg

**GLM 100 C**  
(0 601 072 700)



Capacity	
Laser Diode	: 635 nm, <1mW
Measuring Range*	: 0.05 - 100 m
Measuring Accuracy	: ± 1.5mm
Measuring Units	: mm, cm, m, ft, in
Batteries	: Lithium-Ion
Dust and Splash Protection	: IP54
Weight	: 0.14 kg

**GLM 150**  
(0 601 072 070)



Capacity	
Laser Diode	: 635 nm, <1mW
Measuring Range*	: 0.05 - 150 m
Measuring Accuracy	: ± 1 mm
Measuring Units	: mm, cm, m, ft, in
Batteries	: 4 x 1.5 V LR03(AAA)
Voltage	: 6 VDC
Weight	: 0.24 kg

**GLM 250 VF**  
(0 601 072 170)



Capacity	
Laser Diode	: 635 nm, <1mW
Measuring Range*	: 0.05 - 250 m
Measuring Accuracy	: ± 1 mm
Measuring Units	: m, cm, ft, in
Batteries	: 4 x 1.5 V LR03(AAA)
Weight	: 0.24 kg

## Thermo Detector

**GIS 1000 C**  
(0 601 083 340)



Capacity	
Laser Diode	: 635 nm, <1mW
Working Range*	: 0.1 - 5 m
Measuring Range*	: - 40°C to + 1000°C
Measuring accuracy	: ± 1.0°C (0°C - 100°C)
Batteries	: 4 x 1.5 V LR6(AA) / 10.8 V
Relative Humidity	: 0 - 100 %
Accuracy	: ± 2 %
Storage Medium	: 200 images
Weight	: 0.6 kg

## Cordless Inspection Camera

**GIC 120**  
(0 601 241 100)



Capacity	
Batteries	: 4 x 1.5 V (AA)
Display size	: 2.7"
Display Resolution	: 320 x 240 px
Dia. of camera head	: 8.5 mm
Length of camera cable	: 120 cm
Weight	: 0.5 kg

**GIC 120 C**  
(0 601 240 2K0)



Capacity	
Batteries	: 4 x 1.5 V (AA) or 10.8 V-LI
Display size	: 3.5"
Display resolution	: 320 x 240 px
SD card storage	: Yes
Photo & video mode	: Yes
Dia. of camera head	: 8.5 mm
Length of camera cable	: 120 cm
Weight	: 0.6 kg

## Detector

**GMS 120**  
(0 601 081 000)



Capacity	
Max. Measuring Depth	: 120 mm
Live cables	: 50 mm
Wooden beams	: 38 mm
Metal (magnetic)	: 120 mm
Metal (non-magnetic)	: 80 mm
Batteries	: 1 x 9 V 6LR61
Weight	: 0.27 kg

**D-tect 120**  
(0 601 081 3K0)



Capacity	
Detection Mode	: Universal, Concrete, Drywall
Detection Object	: Ferrous metals, non-ferrous metals, live cables, wooden objects and water-filled plastic pipes
Max. Detection Depth	: 120 mm
Accuracy	: ± 10 mm
Batteries	: 4 x 1.5 V LR6(AA) or 10.8 V
Weight, approx	: 0.5 kg

**D-tect 150 SV**  
(0 601 010 008)



Capacity	
Max. Measuring Depth	: 150 mm
Accuracy	: ± 5 mm
Batteries	: 4 x 1.5 V LR6(AA)
Detectable Materials	: Plastic pipes, cables of all kinds, ferrous/non-ferrous metals, wood, cavities.
Weight	: 0.7 kg

## Line Laser

**GLL 1 P**  
(0 601 066 CB0)



Capacity	
Laser Diode	: 635-650nm, 1mW
Working Range*	: 5 m
Mount Thread Size	: 1/4"
Leveling Accuracy*	: ± 0.5 mm/m (at 0°)
Batteries	: 2 x 1.5 V LR03(AAA)
Weight	: 0.1 kg

**GLL 3-80 P**  
(0 601 063 30A)



Capacity	
Laser Diode	: 640 nm, <1mW
Working Range*	: 20 m
Working Range With Receiver*	: 5 - 80 m (diameter)
Leveling Accuracy*	: ± 0.2 mm / m
Plane	: 3
Tripod Mount	: 1/4", 5/8"
Batteries	: 4 x 1.5 V LR6(AA)
Weight	: 0.76 kg

\* The working range can be decreased by unfavorable environment conditions (eg. Direct sun irradiation).



### Line Laser

**GLL 3-15 X (Bare)**  
(0 601 063 M80)



Capacity	
Laser Diode	: 630 - 650 nm, <1mW
Working Range*	: 15 m
Leveling Accuracy*	: ± 0.2 mm / m
Self-levelling Range	: ± 3°
Tripod Mount	: 5/8"
Batteries	: 4 x 1.5 V LR6(AA)
Weight	: 0.5 kg

**GLL 5-50 X (Bare)**  
(0 601 063 N80)



Capacity	
Laser Diode	: 630 - 650 nm, <1mW
Working Range*	: 15 m
Working Range	
With Receiver*	: 5 - 50 m
Leveling Accuracy*	: ± 0.2 mm / m
Self-levelling Range	: ± 3°
Tripod Mount	: 5/8"
Batteries	: 4 x 1.5 V LR6(AA)
Weight	: 0.5 kg

### Electronic Line Laser

**GLL 5-40 E**  
(0 601 063 GB1)



Capacity	
Laser Diode	: 635 - 650 nm, <1mW
Working Range*	: 15 m
Working Range With Receiver*	: 40 m
Leveling Accuracy	: ± 0.1 mm / m
Self-levelling Range	: ± 3°
Tripod Mount	: 5/8"
Batteries	: 4 x 1.5 V LR6(AA)
Weight	: 1.1 kg

**GLL 8-40 E**  
(0 601 063 HB1)



Capacity	
Laser Diode	: 635 - 650 nm, <1mW
Working Range*	: 15 m
Working Range With Receiver*	: 40 m
Leveling Accuracy	: ± 0.1 mm / m
Self-levelling Range	: ± 3°
Tripod Mount	: 5/8"
Batteries	: 4 x 1.5 V LR6(AA)
Weight	: 1.1 kg

### Combi Laser

**GCL 2-15 G**  
(0 601 066 J00)



Capacity	
Laser Diode	: 635 - 650 nm, <1mW
Working Range*	: 10 m
Dust and splash protection	: IP 54
Leveling Accuracy	: ± 0.3 mm / m
Self-levelling Range	: ± 4°
Tripod Mount	: 1/4", 5/8"
Batteries	: 3 x 1.5 V LR6 (AA)
Weight	: 0.49 kg

**GCL 2-50 CG**  
(0 601 066 H80)



Capacity	
Laser Diode	: 635 - 650 nm, <1mW
Working Range*	: 50 m
Dust and splash protection	: IP 54
Leveling Accuracy	: ± 0.3 mm / m
Self-levelling Range	: ± 4°
Tripod Mount	: 1/4"
Batteries	: 4 x 1.5 V (AA) or Bosch Li-Ion 10.8V / 12V Li-Ion Battery
Weight	: 0.58 kg

### Surface Laser

**GSL 2**  
(0 601 064 002)



Capacity	
Working Range*	: 10 m
Working Range With Target Plate*	: 20 m
Levelling Accuracy*	: 0.3 mm/m
Self-levelling Range	: ± 4°
Batteries	: 10,8 V Li-Ion / 4 x 1.5 V LR6 (AA)
Weight	: 5.77 kg

### Tile Laser

**GTL 3**  
(0 601 015 200)



Capacity	
Laser Diode	: 635 nm, <1mW
Laser Class	: 2
Accuracy	: ± 0.2 mm / m
Accuracy between 45° and 90° - Line	: ± 0.4 mm / m
Batteries	: 4 x 1.5 V LR6(AA)
Weight	: 0.5 kg


### Rotation Laser

**GRL 240 HV**  
(0 601 061 C40)



Capacity	
Laser Diode	: 635 nW, <1mW
Working Range*	: 30 m
Working Range With Receiver*	: 240 m (diameter)
Leveling Accuracy*	: ± 0.2 mm/m
Self-levelling Range	: ± 5°
Batteries	: 2 x 1.5 V LR20(D)
Receiver	: LR 24
Weight	: 1.8 kg

**GRL 300 HVG**  
(0 601 061 703)



Capacity	
Laser Diode	: 532 nm, <5mW
Working Range*	: 50 m
Working Range With Receiver*	: 300 m (diameter)
Leveling Accuracy*	: ± 0.1 mm / m
Batteries	: 2 x 1.5 V LR20(D)
Receiver	: LR 1G
Weight	: 1.8 kg

### Optical Level

**GOL 26 D**  
(0 601 068 000)



Capacity	
Magnification	: 26x
Levelling Accuracy	: 1.6 mm / 30 m
Working Range	: 100 m
Deviation for 1 km double run leveling	: 1.5 mm
Dust and Splash Protection:	: IP 54
Weight	: 1.7 kg

**GOL 32 D**  
(0 601 068 500)



Capacity	
Magnification	: 32x
Levelling Accuracy	: 1 mm / 30 m
Working Range	: 120 m
Deviation for 1 km double run leveling	: 1.0 mm
Dust and Splash Protection:	: IP 54
Weight	: 1.7 kg

### Angle Measurer

**GAM 220**  
(0 601 076 500)



Capacity	
Measurement Range	: 0 - 220°
Accuracy, Angles	: ±0.1°
Leg Length	: 40 cm
Batteries	: 4 x 1.5 V LR6(AA)
Weight	: 1.3 kg

### Digital Inclinometer

**GIM 60 L**  
(0 601 076 900)



Capacity	
Measurement Range	: 0 - 360° (4 x 90°)
Laser working range	: 30 m
Electronics Measurement Accuracy 0° / 90°	: ± 0.05°
Electronics Measurement Accuracy at 1° - 89°	: ± 0.2°
Batteries (Grade measurement):	: 1 x 9V 6LR61
(Laser Operation)	: 2 x AAA LR03
Weight	: 0.9 kg

**GIM 120**  
(0 601 076 800)



Capacity	
Measurement Range	: 0 - 360° (4 x 90°)
Electronics Measurement Accuracy 0° / 90°	: ± 0.05°
Electronics Measurement Accuracy at 1° - 89°	: ± 0.2°
Length	: 1250 mm
Batteries	: 4 x 1.5 V LR6(AA)
Weight	: 1.4 kg

### Measuring Rail

**R 60**



Capacity	
Comes complete with	: Protective Case, Charger, Manufacturer's Certificate
Measuring Range	: 0 - 360°
Accuracy of inclinometer	: ± 0.2°
Audible Signals	: at 0° and 90°
Dimensions (L/W/H)	: 610 x 58 x 30 mm

\* The working range can be decreased by unfavorable environment conditions (eg. Direct sun irradiation).

## Laser Receiver

**LR 1G (for GRL 300 HVG)**  
(0 601 069 700)



Capacity	
Working Range	: 0 - 150 m
Measuring Accuracy (fine/rough)	: ± 1 mm / ± 3 mm
Dust and Splash Protection	: IP 65
Batteries	: 1 x 9 V 6LR61
Weight	: 0.36 kg

**LR 2 (for GLL 5-50, 2-80 P, 3-80 P)**  
(0 601 069 100)



Capacity	
Working Range	: 5 - 80 m
Measurement Accuracy, Fine	: 1 mm
Measurement Accuracy, Rough	: 3 mm
Batteries	: 1 x 9 V 6LR61
Weight	: 0.2 kg

**LR 5 (for GLL 5-40 E / GLL 8-40 E)**  
(0 601 069 G80)



Capacity	
Working Range	: 5 - 40 m
Batteries	: 1 x 9 V 6LR61
Dust & Splash Protection	: IP 54

**LR 6 (for GLL 5-50 X)**  
(0 601 069 H00)



Capacity	
Working Range	: 5 - 50 m
Dust & Splash Protection	: IP 54
Measurement Accuracy (fine/Rough)	: ± 1 mm / ± 3 mm
Batteries	: 2 x 1.5 V LR03 (AAA)
Weight	: 0.2 kg

**LR 7 (for GCL 2-50 CG)**  
(0 601 069 J00)

**NEW!**



Capacity	
Working Range	: 5 - 50 m
Dust & Splash Protection	: IP 54
Measurement Accuracy (fine/Rough)	: ± 1 mm / ± 3 mm
Batteries	: 2 x 1.5 V LR6 (AA)
Weight	: 0.15 kg

**LR 24 / LR 30 (for GRL 240 HV)**  
(0 601 069 213)



Capacity	
Receivable Wavelength	: 630 nm
Measuring Accuracy (fine/medium)	: ± 1.5 mm / ± 3 mm
Dust and Splash Protection	: IP 54
Batteries	: 1 x 9 V 6LR61
Weight	: 0.15 kg

## Tripod

**BT 150 (1/4")**  
(0 601 096 B00)



Capacity	
Work Height	: 55 - 157 cm
Tripod Thread	: 1/4"
Weight	: 1.3 kg

**BT 150 (5/8")**  
(0 601 096 C80)



Capacity	
Work Height	: 52 - 154 cm
Tripod Thread	: 5/8"
Weight	: 1.1 kg

**BT 160**  
(0 601 091 200)



Capacity	
Work Height	: 97 - 160 cm
Tripod Thread	: 5/8"
Weight	: 4.1 kg

**BT 170 HD**  
(0 601 091 300)



Capacity	
Work Height	: 107 - 165 cm
Tripod Thread	: 5/8" x 11
Weight	: 5.5 kg

## Optical Level Measuring Rod

**GR 24**  
(0 601 094 100)



Capacity	
Working Range	: 2 m
Unit Of Measure	: m / cm
Weight	: 1.3 kg

**GR 500**  
(0 601 094 300)



Capacity	
Length	: 5.0 m
Unit Of Measure	: m / cm
Weight	: 1.98 kg

## Universal Holder

**BT 350 (c/w bracket & holder)**  
(0 601 015 B00)



Capacity	
Max Height	: 140 - 350 cm
Weight	: 2.5 kg

**BM 1**  
(0 601 015 A01)



Capacity	
Mount Thread	: 1/4"
Weight	: 0.5 kg

## Bracket

**Bracket (for LR 1, LR 1 G, LR 5)**  
(1 608 M00 70F)



**Bracket (for LR 6)**  
(1 608 M00 C1L)



## Accessories

**RM 3 (for GCL 2-50 CG)**  
(0 601 092 800)

**NEW!**



Capacity	
Height	: 120 mm
Length	: 135 mm
Weight	: 0.500 kg

\* The working range can be decreased by unfavorable environment conditions (eg. Direct sun irradiation).

## High Pressure Cleaner

**AQT 33-11**  
(0 600 8A7 6L0)

**Easy**



Capacity	
Motor Output	: 1,300 W
Pressure	: 110 bar
Flow Rate	: 330 l/h
Max. Temp	: 40°C
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 3.8 kg

**EasyAquatak 120**  
(0 600 8A7 9L0)

**Easy**

**NEW!**



Capacity	
Motor Output	: 1,500 W
Pressure	: 120 bar
Flow Rate	: 350 l/h
Max. Temp	: 40°C
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 5 kg

**AQUATAK 35-12 PLUS**  
(0 600 8A7 1L1)

**Universal**



Capacity	
Motor Output	: 1,500 W
Pressure	: 120 bar
Flow Rate	: 350 l/h
Max. Temp	: 40°C
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 5.53 kg

**UniversalAquatak 125**  
(0 600 8A7 AL0)

**Universal**

**NEW!**



Capacity	
Motor Output	: 1,500 W
Pressure	: 125 bar
Flow Rate	: 360 l/h
Max. Temp	: 40°C
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 6.8 kg

**UniversalAquatak 130**  
(0 600 8A7 BL0)

**Universal**

**NEW!**



Capacity	
Motor Output	: 1,700 W
Pressure	: 130 bar
Flow Rate	: 380 l/h
Max. Temp	: 40°C
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 7.8 kg

**AQUATAK 37-13 PLUS**  
(0 600 8A7 2L1)

**Universal**



Capacity	
Motor Output	: 1,700 W
Pressure	: 130 bar
Flow Rate	: 370 l/h
Max. Temp	: 40°C
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 6.53 kg

**AQT 42-13**  
(0 600 8A7 3L0)

**Advanced**



Capacity	
Motor Output	: 1,900 W
Pressure	: 130 bar
Flow Rate	: 420 l/h
Max. Temp	: 40°C
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 10.25 kg

**AQT 45-14 X**  
(0 600 8A7 4L0)

**Advanced**



Capacity	
Motor Output	: 2,100 W
Pressure	: 140 bar
Flow Rate	: 450 l/h
Max. Temp	: 40°C
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 17.60 kg

**AdvancedAquatak 150**  
(0 600 8A7 7L0)

**Advanced**

**NEW!**



Capacity	
Motor Output	: 2,200 W
Pressure	: 150 bar
Flow Rate	: 490 l/h
Max. Temp	: 40°C
Voltage	: 230 / 240 V
Frequency	: 50 / 60 Hz
Weight	: 22.45 kg